Material Safety Data Sheet

Complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200

NFPA Fire: 3
Health: 1
Reactivity: 0

SECTION I - IDENTITY AND MANUFACTURER'S INFORMATION

Manufacturer's Name, Address: **The Fuller Brush Company - P.O. Box 729 - Great Bend, KS 67530**

Product Name: Water Based Stainless Steel Cleaner — Product Number: 9177

Chemical Family: Pressurized emulsion with petroleum distillates — Package Size: 18 oz; 510 g

EPA Reg. No: N/A — Emergency Telephone No. (620) 792-1711

Preparer: Tom Keyse — Date: 05/05/05 — Signature:

SECTION II - HAZARDOUS INGREDIENTS IDENTITY INFORMATION

Hazardous Components	CAS#	OSHA TWA	ACGIH TWA	Percent
*Water	7732-18-5	NE	NE	<55
White mineral oil	8042-47-5	5 mg/m3	5 mg/m3	<21
Odorless mineral spirits	64742-47-8	1200mg/3	1200mg/3	<10
Isobutane	75-28-5	1000 ppm	800 ppm	7
Propane	74-98-6	1000 ppm	1000 ppm	3

SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

No Physical Hazards		Flammable Gas		Flammable Liquid/Solid		Water Reactive	
Combustible		Flammable Aerosol		Pyrophoric		Oxidizer	
Compressed Gas	x	Explosive		Unstable - Reactive:		Organic Peroxide	

Boiling Point, °F: Compressed Gas — Solubility in Water: Dispersible — Evaporation Rate: <1

Vapor Pressure: 40 psig — Specific Gravity (water =1): 0.931 — pH: 10.5

Vapor Density: ND — %Volatiles by Weight: <80

Appearance and Odor: White emulsion

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method): Conc. >200 F — Flammable Limits: LEL: N/A — UEL: N/A

Extinguishing Media: CO_2, Water Foam, Dry Chemical, ABC Fire Extinguisher

Special Fire Fighting Procedures: Keep aerosols cooled to prevent bursting.

Unusual Fire and Explosion Hazards: Contents under pressure: Temperatures in excess of 120 F may cause bursting. Contents of cans contribute combustible materials in the event of a fire.

SECTION V - REACTIVITY DATA

Stability: Unstable [ ] Stable [x] — Conditions to Avoid: None

Incompatibility: (Materials to Avoid) Mix only with water

Hazardous Decomposition Products or Byproducts: With extreme heat or fire, releases typical hydrocarbon decomposition by-products including carbon dioxide and carbon monoxide.

Hazardous Polymerization: May Occur: [ ] Will Not Occur: [x]

Conditions to Avoid: N/A

Comments:

*Added to comply with the Pennsylvania Worker Right to Know Act of 1984 & the New Jersey Worker & Community Right to Know Act of 1983.

Volatile Organic Compounds (VOC's)=19.9% (calculated)

SECTION VI - HEALTH HAZARD DATA

9177

Route (s) of entry:	Inhalation	x	Skin:	x	Eye:	x	Ingestion:	

No Health Hazard		Reproductive toxin		Sensitizer	
Toxic		Irritant		Carcinogen	
Highly Toxic		Corrosive		See Target Organs	x

TARGET ORGANS

Lungs	x	Eyes	x	Blood		Teratogen		Mucous Membranes	x		
Heart		Skin	x	Liver		Central Nervous System	x	Autonomic Nervous System			
Kidney		Prostate		Mutagen		Cardiovascular System		Respiratory System	x		

Carcinogenicity:	None Known	x	NTP:		IARC:		OSHA Regulated	

Medical Conditions Generally Aggravated by Exposure:
None known

Signs and Symptoms of Exposure:
May cause eye or skin irritation. If significant quantity is inhaled or ingested, dizziness, nausea, anesthetic effects may result.

Emergency and First Aid Procedures:
If sprayed in eyes or on skin, rinse with water for 15 minutes. Contact a physician if irritation persists. If swallowed, DO NOT induce vomiting (aspiration hazard). Call a physician or Poison Control Center immediately. If inhaled, remove to fresh air.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:
Mop up, rinse with detergent and water.

Waste Disposal Method:
Do not puncture or incinerate. For single units, wrap in newspaper and dispose in trash container. Dispose of multiple units in accordance with Local, State and Federal Regulations.

Potential EPA Hazardous Waste Code(s): D001

Steps to be taken in handling and storage:
NFPA "Level 2 Aerosols". Do not spray near heat, sparks, or open flame. Store at 40 - 90F. Read and follow label use directions. Keep out of reach of children.

SECTION VIII - CONTROL MEASURES

Respiratory Protection(Specify Type):
Persons working in an unventilated environment should use a respirator with caustic mist cartridge.

Ventilation: Local Exhaust: Required Special: Optional
Mechanical: Optional

Protective Gloves: Recommended Eye Protection: Required

Other Protective Clothing and Equipment:
None required

SECTION IX - SHIPPING INFORMATION

DOT Proper Shipping Name and Number:
Consumer Commodity, ORM-D

NE = Not Established
N/A = Not Applicable